

## **IMAGETEAM™ 3800ESD Series** *Hand Held Linear Imager for ESD Sensitive and Clean Room Applications*



### **Features**

*High Resolution - Reads very high density bar codes 3 mil. and larger.*

*Clean Room Ready - Cleaned and triple bagged for Class 100 environments.*

*Bright, Sharp and Focused Aiming Line - Easy to aim and scan codes in any lighting condition from darkness to full sunlight, tightly stacked bar code sheets, or small, high resolution labels.*

*Solid, Rugged Design - No moving parts inside and solid construction outside deliver years of reliable service in demanding work environments.*

*Powerful, Flexible Architecture - Connects and interfaces to all major PCs and commercial terminals easily and quickly with Windows®-based programming tools or bar code programming menus.*

*Increased Reading Distances - Easily covers the full range of hand held scanning uses in industrial scanning applications.*

*Real World Reading Performance - Accommodates printer induced bar space variation, faded labels, short quiet zones, low contrast codes, dot matrix printing, and multipart forms with higher resolution, better optics, and improved decoding algorithms.*

*5 Year Warranty*

The IMAGETEAM™ 3800ESD is a high performance scanner designed for the stringent requirements of clean room assembly of sensitive electronic components. The IT3800ESD is constructed of conductive materials engineered to eliminate the build up of dangerous static charge on the scanner, and to quickly drain the charge from any other object with which it comes in contact. The IT3800ESD is assembled for use in a Class 100 clean room environment and is triple bagged for proper introduction into the end use environment.

Internal components of the IT3800ESD scanner are isolated from the conductive path formed by the case, output connector shield, and special shielded cable with drain wire. The scanner is rated for discharges up to 15 kV without damage.

Two models are available: the IT3800VHD/ESD which reads very high density bar codes, and the IT3800LR/ESD for more typical applications.

All materials used in the IT3800ESD are tested using the methods described in ASTM D257, Standard Test Methods for Conductance of Insulating Materials. The surface resistivity is rated at less than 10E5 ohms/square. Triboelectric residual charge is measured with a non contact Electrostatic Field Meter and is less than 5 volts on any surface.

To learn how the IT3800ESD can work for you, contact us at any of the locations listed on the back or visit us at [www.hhp.com](http://www.hhp.com).

**Upgrade your image.**



# IMAGETEAM™ 3800ESD Series Specifications

## Performance

<b>Illumination:</b>	630 NM Visible Red LED
<b>Receiving Device:</b>	3648 element linear imager
<b>Reading Distance:</b>	1 in. (2.5 cm) to 8 in. (20.3 cm) on medium density codes
<b>Reading Width:</b>	5 in. (12.7 cm) code width at 7 in. (17.8 cm) distance
<b>Resolution:</b>	
<b>VHD:</b>	3 mil. at 3.5 in. (8.8 cm) distance
<b>LR:</b>	5 mil. at 3.5 in. (8.8 cm) distance
<b>Skew Angle:</b>	±55°
<b>Pitch Angle:</b>	±55°
<b>Horizontal Velocity:</b>	5 in. (12.7 cm) per second
<b>Minimum Reflectance</b>	
<b>Difference:</b>	30%
<b>Scan Rate:</b>	Programmable to 270 scans per second
<b>Decode Rate:</b>	270 decodes per second

## Mechanical/Electrical

<b>Dimensions</b>	
<b>Length:</b>	5.3 in. (13.5 cm)
<b>Height:</b>	6 in. (15.2 cm)
<b>Width:</b>	3.1 in. (7.9 cm)
<b>Weight:</b>	6.3 oz. (179.2 g)
<b>Housing:</b>	Polycarbonate
<b>Power Requirements:</b>	5Vdc ± 10% at scanner
<b>Current Draw:</b>	<u>Scanning</u> <u>Standby</u>
<b>@ 270 s/s</b>	275mA    125mA
<b>@ 67 s/s</b>	150mA    125mA
<b>Power Supply</b>	
<b>Noise Rejection:</b>	Maximum 100mV peak to peak, 10 to 100 kHz

## Environmental

<b>Temperature</b>	
<b>Operating:</b>	+32°F to +122°F (0°C to +50°C)
<b>Storage:</b>	-4°F to 140°F (-40°C to +60°C)
<b>Humidity:</b>	0 to 95%
<b>Mechanical Shock:</b>	Operational after 25 drops from 5 ft. (1.53 m) to concrete
<b>Ambient Illumination:</b>	0 - 70,000 lux
<b>ESD Protection:</b>	Functional after 15kV discharge
<b>Vibration:</b>	Withstands 5G peak from 20 to 300 Hz
<b>Agency:</b>	FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV
<b>MTBF:</b>	per MIL-HDBK-217F Ground Benign exceeds 50,000 hours
<b>Symbolologies:</b>	Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, RSS.
<b>Interfaces:</b>	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, Apple ADB, USB, TTL level serial wedge, TTL level RS-232, wand emulation mode, and includes (HHLC) non decoded laser compatible output.
<b>Warranty:</b>	Five year factory warranty.

## Worldwide Offices

**Offices Serving North America**  
Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America: +1 800 782 4263  
sales@hhp.com  
Charlotte, NC  
Tel: +1 704 998 3998  
or, in North America: +1 800 782 4263  
sales@hhp.com

**Offices Serving Europe, Middle East, and Africa**  
Europe  
Tel: +31 (0) 40 29 01 600  
euro\_sales@hhp.com  
United Kingdom  
Tel: +44 (0) 1 925 240055  
euro\_sales@hhp.com  
Ireland  
Tel: +353 (0) 502 44007  
euro\_sales@hhp.com

France  
Tel: +33 (0) 1 461 04111  
euro\_sales@hhp.com  
Germany  
Tel: +49 (0) 7 477 151377  
euro\_sales@hhp.com  
Spain  
Tel: +34 93 228 76 68  
euro\_sales@hhp.com

**Offices Serving Asia and the Pacific Rim**  
Hong Kong  
Tel: +852 2511 3050/2511 3132  
asia\_sales@hhp.com  
Japan  
Tel: +813 52127392  
asia\_sales@hhp.com

**Offices Serving Latin America**  
Naples, Florida  
Tel: +1 239 263 7600  
la-sales@hhp.com  
São Paulo  
Tel: +55 11 5016 3454  
la-sales@hhp.com  
Rio De Janeiro  
Tel: +55 21 2494 7060  
la-sales@hhp.com

Web Site Address [www.hhp.com](http://www.hhp.com)

Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2002. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.